

[54] **NIGHT VISION DEVICE WAVELENGTH TEST PATTERN**

[75] Inventor: Alan R. Pinkus, Fairborn, Ohio

[73] Assignee: The United States of America as represented by the Secretary of the Air Force, Washington, D.C.

[21] Appl. No.: 500,302

[22] Filed: Jul. 10, 1995

[51] Int. Cl.⁶ G01J 1/42

[52] U.S. Cl. 250/252.1; 250/332; 345/83

[58] Field of Search 250/252.1 A, 332, 250/339.02, 339.05, 495.1; 345/82, 83

[56] References Cited

U.S. PATENT DOCUMENTS

4,271,408	6/1981	Teshima et al.	345/83
4,695,720	9/1987	Ricder et al.	250/252.1 A
4,965,448	10/1990	Morse et al.	250/252.1
4,967,373	10/1990	Ginsburg	345/83
5,070,239	12/1991	Pinkus	250/252.1
5,184,114	2/1993	Brown	345/83
5,200,622	4/1993	Rouchon et al.	250/334
5,204,532	4/1993	Rosenthal	250/341
5,206,511	4/1993	Apperson et al.	250/343
5,323,002	6/1994	Sampsel et al.	250/252.1
5,359,345	10/1994	Hunter	345/83

OTHER PUBLICATIONS

Evershed et al. "A Field Test Set for Night Vision Devices" Optical Engineering/vol. 15 No. 3/May-Jun. 1976, pp. 251-254.

Humphreys "An Image Scanner for Testing Night Vision Systems" Electro-Optics/Laser International/9-11 Mar. 1976/pp. 183-187.

Grinberg et al. "Visible to Infrared Image Converter for Dynamic Infrared Target Simulation Applications" SPIE vol. 226 IIST (1980)/pp. 129-132.

Primary Examiner—Davis L. Willis

Assistant Examiner—Kiet T. Nguyen

Attorney, Agent, or Firm—Gerald B. Hollins; Thomas L. Kunden

[57] ABSTRACT

A night vision device test arrangement for determination of spectral sensitivity field of view and other operating characteristics of night vision devices. The test arrangement includes a controllable array of radiant energy emitters such as narrow-band light emitting diode elements used to display a night vision device test pattern. The displayed test pattern may be located in the infrared or infrared and visible spectrum regions and may be altered by user command to have different configurations including different physical size, shape and array location and different spectral content. Control of the test pattern may employ a computer or a manual selection apparatus. The disclosed apparatus is especially suited to in-the-field GO/NO GO rapid performance verification of night vision device equipment. Military and non-military uses are contemplated.

18 Claims, 4 Drawing Sheets

